



PRODUCT CATALOGUE

VERSION 1 2015



SDX[®] THERMOBOX[®] **- THE ORIGINAL** **MADE IN SWEDEN** **SINCE 1969**



We at SDX[®] Thermobox[®] has been a reliable partner to professional chefs for over 40 years. Our part of your job is to provide security. You can focus on the food and know that from the moment it leaves the kitchen until served, stored it in the best way.

The fresh ingredients and good food must be good when served. You should also feel safe in that the technology works. The temperature is exactly right and that the boxes can withstand the sometimes rugged treatment they may face.

The correct temperature

The single most important factor to maintain the freshness of your food and proper hygiene is the temperature. SDX® Thermobox® keeps the temperature within the desired values and with minimal temperature fluctuations. Combined with highly efficient insulation provides the food quality which is evident in the visitors appreciation.



Low energy consumption

To create the best possible insulation properties the boxes are insulated with polyurethane, which expands under high pressure and joins the outer and inner containers to a strong and well-insulated unit.

This allows the food to be kept at the right temperature with a very low energy consumption and a low operating cost.

Hygienic food handling

The all stainless steel inside without any seams or corners are natural choice for hygienic food handling. Pressed stainless steel guides, a unique technology that provides unmatched durability, increases safety and ease of cleaning.



Ergonomic and economic

The sophisticated design combined with easy rolling wheels make transfer from the kitchen to the dining room simple and ergonomic.

SDX® Thermobox® has a compact and lightweight design. The small footprint saves costly space both in storage and during transportation.

Smooth storage surface
with the possibility for
securing loads

Welded stainless steel inside
containers with smooth
surfaces, high durability and
the best hygiene properties

The doors can
be opened
270 degrees.

Deep drawn guides,
easy cleaning and
increased safety

Short heating
or cooling time.

Air gaps for internal air
circulation and even
temperature distribution

Durable door
gaskets

Electronically
adjustable
temperature control

Easy to clean for
improved hygiene





Protective top frame

High energy efficiency means low operating costs

High-pressure isolation with polyurethane

Choice of door locks by function

Low overall weight

Removable doors

Recessed door for effective insulation

Stable reject list

Jetproof interior and exterior for easier cleaning

Compact space-efficient design

Can be equipped with a central brake

Durable 160mm easy rolling rubber wheels



A complete product range for all your food transportation needs.

We offer a range of products spanning from the simple insulated S-box to advanced cooling and heating systems in the K- and F-boxes.

	<p>THERMOBOX® S - NEUTRAL THERMOBOX</p> <p>SDX can provide a full range of neutral thermobox options which include insulation only.</p>	<p>8</p>
	<p>THERMOBOX® C – ACTIVE COOLING</p> <p>Active cooling refrigeration for storing chilled food over longer periods of time.</p>	<p>14</p>
	<p>THERMOBOX® K – COMPRESSOR COOLING</p> <p>Extremely efficient compressor cooling accounts for the highest standards refrigeration.</p>	<p>18</p>
	<p>THERMOBOX® E – ELECTRIC HEATING</p> <p>Have an advanced heating system with extremely high reliability. It keeps the temperature within the desired values and with minimal temperature fluctuations.</p>	<p>22</p>
	<p>THERMOBOX® F – CONVECTION HEATING</p> <p>Convection heat with added value and many benefits! Short heating time. Hot air fan to compensate temperature losses. Flexible heating cabinet.</p>	<p>26</p>
	<p>THERMOBOX® – COMBINATIONS</p> <p>Transport and storage of both hot and chilled food in the same unit.</p>	<p>32</p>
	<p>PORTABLE THERMOBOX®</p>	<p>46</p>
	<p>TROLLEYS</p>	<p>47</p>
	<p>THERMOBOX® – OPTIONS AND ACCESSORIES</p>	<p>48</p>



THERMOBOX® S

is the simplest product we have. A box, with really good insulation, you cool down by placing it in a cold room or using SDX® cooling plate. With all-welded, stainless steel interior. Unrivalled wear-resistance and easy cleaning with soft-form guides pressed directly into the steel.


S-boxes are great for food to be served cold as for the storage of food to be heated at a later stage in the process.




THERMOBOX® S - NEUTRAL THERMOBOX

A full range of neutral thermobox options which include insulation only.


S60

	GUIDES	OUTER	INNER	WEIGHT
	4 x GN 1/1 80mm spacing	W: 525mm D: 700mm H: 870mm	W: 330mm D: 540mm H: 345mm	37 kg
	Product number: 122005-036 SDX Thermobox S60 (4 GN 1/1)			


S90

	GUIDES	OUTER	INNER	WEIGHT
	6 x GN 1/1 80mm spacing	W: 525mm D: 700mm H: 1030mm	W: 330mm D: 540mm H: 505mm	41 kg
	Product number: 122003-036 SDX Thermobox S90 (6 GN 1/1)			

S120

	GUIDES	OUTER	INNER	WEIGHT
	8 x GN 1/1 80mm spacing	W: 525mm D: 700mm H: 1190mm	W: 330mm D: 540mm H: 665mm	45 kg
	Product number: 122039-036 SDX Thermobox S120 (8 GN 1/1)			

S150

	GUIDES	OUTER	INNER	WEIGHT
	10 x GN 1/1 80mm spacing	W: 525mm D: 700mm H: 1180mm	W: 330mm D: 540mm H: 825mm	47 kg
	Product number: 122040-036 SDX Thermobox S150 (10 GN 1/1)			

THERMOBOX® S - NEUTRAL THERMOBOX

A full range of neutral thermobox options which include insulation only.

S180



GUIDES

12 x GN 1/1
80mm spacing

OUTER

W: 525mm
D: 700mm
H: 1330mm

INNER

W: 330mm
D: 540mm
H: 1000mm

WEIGHT

50 kg

Product number: 122030-036
SDX Thermobox S180 (12 GN 1/1)

SS180



GUIDES

6 + 6 x GN 1/1
80mm spacing

OUTER

W: 525mm
D: 700mm
H: 1330mm

INNER

W: 330mm
D: 540mm
H: 665mm

WEIGHT

60 kg

Product number: 122101-036 SDX
Thermobox SS180 (6+6 GN 1/1)

S210R



GUIDES

14 x GN 1/1
80mm spacing

OUTER

W: 525mm
D: 700mm
H: 1490mm

INNER

W: 330mm
D: 540mm
H: 1160mm

WEIGHT

56 kg

Product number: 122075-036
SDX Thermobox S210 (14 GN 1/1)

SS360



GUIDES

12 + 12 x GN 1/1
80mm spacing

INNER

W: 920mm
D: 700mm
H: 1330mm

OUTER

W: 330+330mm
D: 540mm
H: 1000mm

WEIGHT

100 kg

Product number: 122045-03
SDX Thermobox SS360 (12+12 GN 1/1)

THERMOBOX® S - NEUTRAL THERMOBOX

A full range of neutral thermobox options which include insulation only.

SSS540



GUIDES	OUTER	INNER	WEIGHT
12+12+12 x GN 1/1 80mm spacing	W: 1330mm D: 700mm H: 1330mm	W:330+330+330mm D: 540mm H: 1000mm	150 kg
<p>Product number: 122055-03 SDX Thermobox SSS540 (12+12+12 GN 1/1)</p>			

12 | 12 | 12



THERMOBOX® S - Technical specifications

Exterior walls: ABS plastic.

Inner container: Welded container in stainless steel.

Guides: Stainless steel, pressed from the inner container.

Insulation: Polyurethane foam.

Door: Internal surface made of smooth and seamless stainless steel. Exterior in ABS plastic with bolt lock and door mounted handle for one-handed grip.

Wheels: Hot-dip galvanized steel. 160 mm wheels with rubber tires, two brakes and 2 fixed.

Top frame: Stainless steel and PVC corners.

Trolley frame: Reject list of galvanized steel coated with PVC.



THERMOBOX® S - Optional extras

200mm castors, 2 fixed and 2 swivel castors with brakes	123006
Cooling plate GN 1/1	141003
Towing set	149010
Central brake	123015
Glass door	123017
Analog thermometer in the door	123007
Extra handles, set of 2	212011
Label holder A5	219028

THERMOBOX® S - Banquet edition for great transports

SDX® Thermobox® Banquet is created for you to carry and serve large quantities of food quickly and efficiently. Ideal for stadiums, hotels and conference centers. The box's large volume, combined with several guides creates a flexible and efficient food transport.

BANQUET S



GUIDES	OUTER	INNER	WEIGHT
17 x 2/1 GN 80mm spacing	W: 790mm D: 890mm H: 1740mm	W: 535mm D: 667mm H: 1405mm	122 kg

Product number: 122252-01
SDX Thermobox BANQUET S (17 GN 2/1)

BANQUET SS



GUIDES	OUTER	INNER	WEIGHT
17+17 x 2/1 GN 80mm spacing	W: 1445mm D: 890mm H: 1740mm	W: 535+535mm D: 667mm H: 1405mm	240 kg

Product number: 122253-01
SDX Thermobox BANQUET S (17+17 GN 2/1)

THERMOBOX® S Banquet - Technical specifications

Exterior walls: Aluminium

Inner container: Welded container in aluminium.

Guides: Stainless steel guides with rivets.

Insulation: Polyurethane foam.

Door: Internal surface made of smooth and seamless stainless steel. Exterior in aluminium with bolt lock and door mounted handle for one-handed grip.

Wheels: Hot-dip galvanized steel. 160 mm wheels with rubber tires, two braked and two fixed. Banquet SS box has six wheels, two braked and four fixed

Trolley frame: Reject list of galvanized steel coated with PVC.







THERMOBOX® C

with active cooling has an advanced cooling system with extremely high reliability. It keeps the temperature within the desired values and with minimal temperature fluctuations. Combined with highly efficient insulation provides the food quality which is evident in the visitors appreciation.



THERMOBOX® C – ACTIVE COOLING

Active cooling refrigeration for storing chilled food over longer periods of time.

C60



GUIDES

4 x GN 1/1
80mm spacing

OUTER

W: 525mm
D: 810mm
H: 895mm

INNER

W: 330mm
D: 540mm
H: 370mm

WEIGHT

51 kg

Product number: 122206-03
SDX Thermobox C60 (4 GN 1/1)

4

C90



GUIDES

6 x GN 1/1
80mm spacing

OUTER

W: 525mm
D: 810mm
H: 1052mm

INNER

W: 330mm
D: 540mm
H: 500mm

WEIGHT

56 kg

Product number: 122207-03
SDX Thermobox C90 (6 GN 1/1)

6

C120



GUIDES

8 x GN 1/1
80mm spacing

OUTER

W: 525mm
D: 810mm
H: 1187mm

INNER

W: 330mm
D: 540mm
H: 660mm

WEIGHT

60 kg

Product number: 122205-03
SDX Thermobox C120 (8 GN 1/1)

8

C150



GUIDES

10 x GN 1/1
80mm spacing

OUTER

W: 525mm
D: 825mm
H: 1205mm

INNER

W: 330mm
D: 540mm
H: 825mm

WEIGHT


65 kg


Product number: 122208-036
SDX Thermobox C150 (10 GN 1/1)


10


THERMOBOX® C – ACTIVE COOLING

Active cooling refrigeration for storing chilled food over longer periods of time.

	GUIDES	OUTER	INNER	WEIGHT
	12 x GN 1/1 80mm spacing	W: 525mm D: 825mm H: 1360mm	W: 330mm D: 540mm H: 1000mm	70 kg
	Product number: 122200-03 SDX Thermobox C180 (12 GN 1/1)			

	GUIDES	OUTER	INNER	WEIGHT
	14 x GN 1/1 80mm spacing	W: 525mm D: 825mm H: 1515mm	W: 330mm D: 540mm H: 1160mm	75 kg
	Product number: 122209-03 SDX Thermobox C210 (14 GN 1/1)			

	GUIDES	OUTER	INNER	WEIGHT
	8+8 x GN 1/1 80mm spacing	W: 920mm D: 810mm H: 1215mm	W: 330+330mm D: 540mm H: 665mm	120 kg
	Product number: 122320-03 SDX Thermobox CC240 (8+8 GN 1/1)			

	GUIDES	OUTER	INNER	WEIGHT
	12+12 x GN 1/1 80mm spacing	W: 920mm D: 825mm H: 1355mm	W: 330+330mm D: 540mm H: 1000mm	140 kg
	Product number: 122201-03 SDX Thermobox CC360 (12+12 GN 1/1)			

12

14

8 8

12 12

THERMOBOX® C – ACTIVE COOLING

Active cooling refrigeration for storing chilled food over longer periods of time.

CC420



GUIDES

14+14 x GN 1/1
80mm spacing

OUTER

W: 920mm
D: 825mm
H: 1515mm

INNER

W: 330+330mm
D: 540mm
H: 1160mm

WEIGHT

150 kg

Product number: 122265-03
SDX Thermobox CC420 (14+14 GN 1/1)

CCC540



GUIDES

12+12+12 x GN
1/1
80mm spacing

OUTER

W: 1330mm
D: 825mm
H: 1355mm

INNER

W: 330+330+330mm
D: 540mm
H: 1000mm

WEIGHT

210 kg

Product number: 122266-03
SDX Thermobox CCC540 (12+12+12 GN 1/1)



THERMOBOX® C - Technical specifications

Exterior walls: ABS plastic.

Inner container: Welded container in stainless steel.

Guides: Stainless steel, pressed from the inner container.

Insulation: Polyurethane foam.

Door: Internal surface made of smooth and seamless stainless steel. Exterior in ABS plastic with bolt lock and door mounted handle for one-handed grip.

Wheels: Hot-dip galvanized steel. 160 mm wheels with rubber tires, two brakes and 2 fixed. CCC540 box has six wheels, two braked and four fixed.

Top frame: Stainless steel and PVC corners.

Trolley frame: Rejected list of galvanized steel coated with PVC.

C: Efficient compact chillers with electronic temperature control AA120, 27 V DC. 230V/245W AC, insulation class IP44.



THERMOBOX® C - Optional extras

200mm castors, 2 fixed and 2 swivel castors with brakes	123006
Towing set	149010
Central brake	123015
Glass door	123017
Extra handles, set of 2	212011
Label holder A5	219028
Eccentric lock	123023
Supporting castor for towing set	149014



THERMOBOX® K

Extremely efficient compressor cooling accounts for the highest standards of refrigeration.

The stream of cool air creates a cold buffer around each level of the food, eliminating the risk of unwanted temperature rise. Through the efficient flow of air provides a uniform temperature throughout the box.

With the same volume of the box is cooled from +25 °C to +2 °C in a fraction of the time for an ordinary Thermobox® C with active cooling.



THERMOBOX® K – COMPRESSOR COOLING

K180



GUIDES

OUTER

INNER

WEIGHT

12 x GN 1/1
80mm spacing

W: 525mm
D: 765mm
H: 1605mm

W: 330mm
D: 540mm
H: 1000mm

95 kg

Product number: 122270-03
SDX Thermobox K180 (12 GN 1/1)

THERMOBOX® K - Technical specifications

Exterior walls: ABS plastic.

Inner container: Welded container in stainless steel.

Guides: Stainless steel, pressed from the inner container.

Insulation: Polyurethane foam.

Door: Internal surface made of smooth and seamless stainless steel. Exterior in ABS plastic with bolt lock and door mounted handle for one-handed grip.

Wheels: Hot-dip galvanized steel. 160 mm wheels with rubber tires, two brakes and 2 fixed.

Top frame: Stainless steel and PVC corners.

Trolley frame: Reject list of galvanized steel coated with PVC.

K: Efficient convection cooling with electronic temperature control 230V/245W/1.8A, insulation class IP44.

THERMOBOX® K - Optional extras

200mm castors, 2 fixed and 2 swivel castors with brakes	123006
Towing set	149010
Central brake	123015
Glass door	123017
Extra handles, set of 2	212011
Label holder A5	219028

THERMOBOX® K - Banquet edition for great transports

SDX® Thermobox® Banquet is created for you to carry and serve large quantities of food quickly and efficiently. Ideal for stadiums, hotels and conference centers. The box's large volume, combined with several guides creates a flexible and efficient food transport.

BANQUET K



GUIDES	OUTER	INNER	WEIGHT
13 x 2/1 GN 80mm spacing	W: 790mm D: 890mm H: 1740mm	W: 535mm D: 667mm H: 1120mm	138 kg
Effect: 230V/246W Product number: 122252-01K SDX Thermobox BANQUET K (13 GN 2/1)			

BANQUET KK



GUIDES	OUTER	INNER	WEIGHT
13+13 x 2/1 GN 80mm spacing	W: 1450mm D: 890mm H: 1740mm	W: 535+535mm D: 667mm H: 1120mm	276 kg
Effect: 230V/246W Product number: 122254-01K SDX Thermobox BANQUET KK (13+13 GN 2/1)			



THERMOBOX® K Banquet - Technical specifications

Exterior walls: Aluminium

Inner container: Welded container in aluminium.

Guides: Stainless steel guides with rivets.

Insulation: Polyurethane foam.

Door: Internal surface made of smooth and seamless aluminium. Exterior in aluminium with bolt lock and door mounted handle for one-handed grip.

Wheels: Hot-dip galvanized steel. 160 mm wheels with rubber tires, two braked and two fixed. Banquet KK box has six wheels, two braked and four fixed.

Trolley frame: Reject list of galvanized steel coated with PVC.

K: Efficient convection cooling with electronic temperature control 230V/245W, insulation class IP44.





THERMOBOX® E


Have an advanced heating system with extremely high reliability. It keeps the temperature within the desired values and with minimal temperature fluctuations. Combined with highly efficient insulation provides the food quality which is evident in the visitors appreciation.





Have an advanced heating system with extremely high reliability. It keeps the temperature within the desired values and with minimal temperature fluctuations.

E60	GUIDES	OUTER	INNER	WEIGHT
	4 x GN 1/1 80mm spacing	W: 525mm D: 700mm H: 895mm	W: 330mm D: 540mm H: 345mm	41 kg
	230V/280W Product number: 122006-036 SDX Thermobox E60 (4 GN 1/1)			

E90	GUIDES	OUTER	INNER	WEIGHT
	6 x GN 1/1 80mm spacing	W: 525mm D: 700mm H: 1055mm	W: 330mm D: 540mm H: 505mm	45 kg
	230V/500W Product number: 122004-036 SDX Thermobox E90 (6 GN 1/1)			


E120	GUIDES	OUTER	INNER	WEIGHT
	8 x GN 1/1 80mm spacing	W: 525mm D: 700mm H: 1215mm	W: 330mm D: 540mm H: 665mm	48 kg
	230V/500W Product number: 122027-036 SDX Thermobox E120 (8 GN 1/1)			


EE120	GUIDES	OUTER	INNER	WEIGHT
	4+4 x GN 1/1 80mm spacing	W: 525mm D: 700mm H: 1190mm	W: 330mm D: 540mm H: 348+348mm	54 kg
	2 x 230V/280W Product number: 122013-036 SDX Thermobox EE120 (4+4 GN 1/1)			


EE150	GUIDES	OUTER	INNER	WEIGHT
	6+4 x GN 1/1 80mm spacing	W: 525mm D: 700mm H: 1350mm	W: 330mm D: 540mm H: 348+508mm	56 kg
	230V/500W + 230V/280W Product number: 122062-036 SDX Thermobox EE150 (6+4 GN 1/1)			


THERMOBOX® E – ELECTRIC HEATING


Have an advanced heating system with extremely high reliability. It keeps the temperature within the desired values and with minimal temperature fluctuations.

	GUIDES	OUTER	INNER	WEIGHT
	12 x GN 1/1 80mm spacing	W: 525mm D: 700mm H: 1355mm	W: 330mm D: 540mm H: 1000mm	60 kg
	230V/800W Product number: 122033-036 SDX Thermobox E180 (12 GN 1/1)			

	GUIDES	OUTER	INNER	WEIGHT
	8+4 x GN 1/1 80mm spacing	W: 525mm D: 700mm H: 1635mm	W: 330mm D: 540mm H: 668+348mm	60 kg
	230V/500W + 230V/280W Product number: 122104-036 SDX Thermobox EE180 (8+4 GN 1/1)			

	GUIDES	OUTER	INNER	WEIGHT
	6+6 x GN 1/1 80mm spacing	W: 525mm D: 700mm H: 1510mm	W: 330mm D: 540mm H: 508+508mm	70 kg
	230V/500W + 230V/500W Product number: 122102-036 SDX Thermobox EE180 (6+6 GN 1/1)			

	GUIDES	OUTER	INNER	WEIGHT
	8+6 GN 1/1 80mm spacing	W: 525mm D: 700mm H: 1955mm	W: 330mm D: 540mm H: 668+508mm	74 kg
	230V/500W + 230V/500W Product number: 122155-036 SDX Thermobox EE210 (8+6 GN 1/1)			

	GUIDES	OUTER	INNER	WEIGHT
	8+8 x GN 1/1 80mm spacing	W: 920mm D: 700mm H: 1215mm	W: 330+330mm D: 540mm H: 665mm	96 kg
	2 x 230V/500W Product number: 122132-036 SDX Thermobox EE240 (8+8 GN 1/1)			

Have an advanced heating system with extremely high reliability. It keeps the temperature within the desired values and with minimal temperature fluctuations.

EE360



GUIDES	OUTER	INNER	WEIGHT
12+12 x GN 1/1 80mm spacing	W: 920mm D: 700mm H: 1355mm	W: 330+330mm D: 540mm H: 1000mm	120 kg
2 x 230V/800W Product number: 122048-03 SDX Thermobox EE360 (12+12 GN 1/1)			

12|12

EEE540



GUIDES	OUTER	INNER	WEIGHT
12+12+12 x GN 1/1 80mm spacing	W: 920mm D: 700mm H: 1355mm	W: 330+330+330mm D: 540mm H: 1000mm	180 kg
3 x 230V/800W Product number: 122050-031 SDX Thermobox EEE540 (12+12+12 GN 1/1)			

12|12|12



THERMOBOX® E - Technical specifications

Exterior walls: ABS plastic.
Inner container: Welded container in stainless steel.
Guides: Stainless steel, pressed from the inner container.
Insulation: Polyurethane foam.
Door: Internal surface made of smooth and seamless stainless steel. Exterior in ABS plastic with bolt lock and door mounted handle for one-handed grip.

Wheels: Hot-dip galvanized steel. 160 mm wheels with rubber tires, two brakes and 2 fixed.
Top frame: Stainless steel and PVC corners.
Trolley frame: Rejected list of galvanized steel coated with PVC.
E: Patented, efficient heating system, with electronic temperature control Foil elements, insulation class IP 44, 230V/800W. CE and S mark.



THERMOBOX® E - Optional extras

200mm castors, 2 fixed and 2 swivel castors with brakes	123006
Towing set	149010
Central brake	123015
Glass door	123017
Extra handles, set of 2	212011
Label holder A5	219028



THERMOBOX® F

Convection heat with added value and many benefits!


Short heating time. Hot air fan to compensate temperature losses. Flexible heating cabinet.




THERMOBOX® F – CONVECTION HEATING

Convection heat with added value and many benefits! Short heating time. Hot air fan to compensate temperature losses. Flexible heating cabinet.


F90

	GUIDES	OUTER	INNER	WEIGHT
	6 x GN 1/1 80mm spacing	W: 525mm D: 770mm H: 1055mm	W: 330mm D: 540mm H: 508mm	54 kg
	230V/1000W Product number: 122004-036F SDX Thermobox F90 (6 GN 1/1)			


F120

	GUIDES	OUTER	INNER	WEIGHT
	8 x GN 1/1 80mm spacing	W: 525mm D: 770mm H: 1215mm	W: 330mm D: 540mm H: 668mm	57 kg
	230V/1000W Product number: 122027-036F SDX Thermobox F120 (8 GN 1/1)			

F150

	GUIDES	OUTER	INNER	WEIGHT
	10 x GN 1/1 80mm spacing	W: 525mm D: 770mm H: 1180mm	W: 330mm D: 540mm H: 828mm	61 kg
	230V/1000W Product number: 122064-036F SDX Thermobox F150 (10 GN 1/1)			

F180

	GUIDES	OUTER	INNER	WEIGHT
	12 x GN 1/1 80mm spacing	W: 525mm D: 770mm H: 1355mm	W: 330mm D: 540mm H: 1000mm	65 kg
	230V/1000W Product number: 122033-036F SDX Thermobox F180 (12 GN 1/1)			

FF180

	GUIDES	OUTER	INNER	WEIGHT
	6+6 x GN 1/1 80mm spacing	W: 525mm D: 770mm H: 1510mm	W: 330mm D: 540mm H: 508+508mm	65 kg
	2x230V/1000W Product number: 122134-036F SDX Thermobox FF180 (6+6 GN 1/1)			

6

8

10


12


6


6


THERMOBOX® F – CONVECTION HEATING

Convection heat with added value and many benefits! Short heating time. Hot air fan to compensate temperature losses. Flexible heating cabinet.

	GUIDES	OUTER	INNER	WEIGHT
F210 	14 x GN 1/1 80mm spacing	W: 525mm D: 770mm H: 1515mm	W: 330mm D: 540mm H: 1160mm	70 kg
	230V/1000W Product number: 122070-036F SDX Thermobox F210 (14 GN 1/1)			

	GUIDES	OUTER	INNER	WEIGHT
FF210 	8+6 x GN 1/1 80mm spacing	W: 525mm D: 770mm H: 1955mm	W: 330mm D: 540mm H: 668+508mm	70 kg
	2x230V/1000W Product number: 122135-036F SDX Thermobox FF210 (8+6 GN 1/1)			

	GUIDES	OUTER	INNER	WEIGHT
FF240 	8+8 x GN 1/1 80mm spacing	W: 920mm D: 770mm H: 1190mm	W: 330+330mm D: 540mm H: 668+668mm	110 kg
	2 x 230V/1000W Product number: 122132-036F SDX Thermobox FF240 (8+8 GN 1/1)			

	GUIDES	OUTER	INNER	WEIGHT
FF360 	12+12 x GN 1/1 80mm spacing	W: 920mm D: 770mm H: 1355mm	W: 330+330mm D: 540mm H: 1000mm	130 kg
	2 x 230V/1000W Product number: 122048-036F SDX Thermobox FF360 (12+12 GN 1/1)			

THERMOBOX® F – CONVECTION HEATING

Convection heat with added value and many benefits! Short heating time. Hot air fan to compensate temperature losses. Flexible heating cabinet.

FF420



GUIDES	OUTER	INNER	WEIGHT
14+14 x GN 1/1 80mm spacing	W: 920mm D: 770mm H: 1515mm	W: 330+330mm D: 540mm H: 1160mm	140 kg

2 x 230V/1000W
Product number: 122057-036F
 SDX Thermobox FF420 (14+14 GN 1/1)

14 | 14

FFF540



GUIDES	OUTER	INNER	WEIGHT
12+12+12 x GN 1/1 80mm spacing	W: 1335mm D: 770mm H: 1355mm	W: 330+330+330mm D: 540mm H: 1000mm	195 kg

3 x 230V/1000W
Product number: 122136-036F
 SDX Thermobox FFF540 (12+12+12 GN 1/1)

12 | 12 | 12



THERMOBOX® F - Technical specifications

Exterior walls: ABS plastic.

Inner container: Welded container in stainless steel.

Guides: Stainless steel, pressed from the inner container.

Insulation: Polyurethane foam.

Door: Internal surface made of smooth and seamless stainless steel. Exterior in ABS plastic with bolt lock and door mounted handle for one-handed grip.

Wheels: Hot-dip galvanized steel. 160 mm wheels with rubber tires, two brakes and 2 fixed.

Top frame: Stainless steel and PVC corners.

Trolley frame: Reject list of galvanized steel coated with PVC.

F: Efficient convection heating system, with electronic temperature control, insulation class IP 44, 230V/1000W. CE and S mark.



THERMOBOX® F - Optional extras

200mm castors, 2 fixed and 2 swivel castors with brakes	123006
Towing set	149010
Central brake	123015
Glass door	123017
Extra handles, set of 2	212011
Label holder A5	219028
Eccentric lock	123023
Supporting castor for towing set	149014

THERMOBOX® F - Banquet edition for great transports

SDX® Thermobox® Banquet is created for you to carry and serve large quantities of food quickly and efficiently. Ideal for stadiums, hotels and conference centers. The box's large volume, combined with several guides creates a flexible and efficient food transport.

BANQUET F	GUIDES	OUTER	INNER	WEIGHT
	17 x GN 2/1 80mm spacing	W: 790mm D: 890mm H: 1740mm	W: 535mm D: 667mm H: 1405mm	127 kg
	2 x 230V/1350W/6A Product number: 122252-01F SDX Thermobox Banquet F (17 GN 2/1)			

BANQUET FF	GUIDES	OUTER	INNER	WEIGHT
	17+17 x GN2/1 80mm spacing	W: 1445mm D: 890mm H: 1740mm	W:535+535mm D: 667mm H: 1405mm	254 kg
	2 x 230V/1350W/6A Product number: 122256-01F SDX Thermobox Banquet FF (17+17 GN 2/1)			

THERMOBOX® F Banquet - Technical specifications

Exterior walls: Aluminium

Inner container: Welded container in aluminium.

Guides: Stainless steel guides with rivets.

Insulation: Polyurethane foam.

Door: Internal surface made of smooth and seamless stainless steel. Exterior in aluminium with bolt lock and door mounted handle for one-handed grip.

Wheels: Hot-dip galvanized steel. 160 mm wheels with rubber tires, two braked and two fixed. Banquet KK box has six wheels, two braked and four fixed

Trolley frame: Reject list of galvanized steel coated with PVC.

F: Efficient convection heating system, with electronic temperature control, insulation class IP 44, 230V/1350W. CE and S mark.





Sophisticated in both big and small

At SDX® Thermobox® we are both conservative and innovative at the same time. We utilize the latest technology and we listen closely to the wishes of our customers, but we do not make any changes before we are truly convinced that they also bring improvements.

We are meticulous in all aspects should be analyzed. The ergonomic, functional and especially those related to longevity and durability.

We are convinced that the most important thing for you as professional chefs is that you can be sure that the boxes work day after day and the food always keeps the temperature you've decided. There are many reasons to be careful in every detail.





A SUCCESSFUL COMBINATION!

Transport and storage of both hot and chilled food in the same unit.

To meet different needs, SDX® has many solutions for a successful combination with cooling and heating in the same Thermobox® with or without active cooling or electronic heating.

All variants have the renowned quality of SDX® and contains all-stainless steel interiors i.e., pressed guides in stainless inner receptacles.





**THERMOBOX® SE – NEUTRAL AND
ELECTRIC HEATING COMBINATION**

34



**THERMOBOX® SF – NEUTRAL AND
CONVECTION HEATING COMBINATION**

36



**THERMOBOX® CE – ACTIV COOLING AND
ELECTRIC HEATING COMBINATION**

38



**THERMOBOX® CF – ACTIV COOLING AND
CONVECTION HEATING COMBINATION**

40



**THERMOBOX® KE – COMPRESSOR COOLING AND
ELECTRIC HEATING COMBINATION**

42



**THERMOBOX® KF – COMPRESSOR COOLING AND
CONVECTION HEATING COMBINATION**

44

THERMOBOX® SE – NEUTRAL AND ELECTRIC HEATING COMBINATION

SE120



GUIDES	OUTER	INNER S	INNER E	WEIGHT
4+4 x GN 1/1 80mm spacing	W: 525mm D: 700mm H: 1190mm	W: 330mm D: 540mm H: 348mm	W: 330mm D: 540mm H: 348mm	52 kg

Neutral + 230V/280W
Product number: 122010-036
 SDX Thermobox SE120 (4+4 GN 1/1)

SE150



GUIDES	OUTER	INNER S	INNER E	WEIGHT
4+6 x GN 1/1 80mm spacing	W: 525mm D: 700mm H: 1350mm	W: 330mm D: 540mm H: 348mm	W: 330mm D: 540mm H: 505mm	56 kg

Neutral + 230V/500W
Product number: 122060-036
 SDX Thermobox SE150 (4+6 GN 1/1)

SE180



GUIDES	OUTER	INNER S	INNER E	WEIGHT
4+8 x GN 1/1 80mm spacing	W: 525mm D: 700mm H: 1635mm	W: 330mm D: 540mm H: 348mm	W: 330mm D: 540mm H: 668mm	60 kg

Neutral + 230V/500W
Product number: 122105-036
 SDX Thermobox SE180 (4+8 GN 1/1)

SE180



GUIDES	OUTER	INNER S	INNER E	WEIGHT
6+6 x GN 1/1 80mm spacing	W: 525mm D: 700mm H: 1510mm	W: 330mm D: 540mm H: 508mm	W: 330mm D: 540mm H: 508mm	63 kg

Neutral + 230V/500W
Product number: 122100-036
 SDX Thermobox SE180 (6+6 GN 1/1)

THERMOBOX® SE – NEUTRAL AND ELECTRIC HEATING COMBINATION

SE210

	GUIDES	OUTER	INNER S	INNER E	WEIGHT
	6+8 x GN 1/1 80mm spacing	W: 525mm D: 700mm H: 1955mm	W: 330mm D: 540mm H: 508mm	W: 330mm D: 540mm H: 668mm	67 kg
	Neutral + 230V/500W Product number: 122151-036 SDX Thermobox SE210 (6+8 GN 1/1)				

SE240

	GUIDES	OUTER	INNER S	INNER E	WEIGHT
	8+8 x GN 1/1 80mm spacing	W: 920mm D: 700mm H: 1190mm	W: 330mm D: 540mm H: 668mm	W: 330mm D: 540mm H: 668mm	86 kg
	Neutral + 230V/500W Product number: 122130-03 SDX Thermobox SE240 (8+8 GN 1/1)				

SE360

	GUIDES	OUTER	INNER S	INNER E	WEIGHT
	12+12 x GN 1/1 80mm spacing	W: 920mm D: 700mm H: 1355mm	W: 330mm D: 540mm H: 1000mm	W: 330mm D: 540mm H: 1000mm	104 kg
	Neutral + 230V/800W Product number: 122046-03 SDX Thermobox SE360 (12+12 GN 1/1)				



THERMOBOX® SE - Technical specifications

Exterior walls: ABS plastic.

Inner container: Welded container in stainless steel.

Guides: Stainless steel, pressed from the inner container.

Insulation: Polyurethane foam.

Door: Internal surface made of smooth and seamless stainless steel. Exterior in ABS plastic with bolt lock and door mounted handle for one-handed grip.

Wheels: Hot-dip galvanized steel. 160 mm wheels with rubber

tires, two brakes and 2 fixed.

Top frame: Stainless steel and PVC corners.

Trolley frame: Reject list of galvanized steel coated with PVC.

S: Neutral

E: Patented, efficient heating system, with electronic temperature control Foil elements, insulation class IP 44, 230V/800W. CE and S mark.

THERMOBOX® SF – NEUTRAL AND CONVECTION HEATING COMBINATION

SF150



GUIDES	OUTER	INNER S	INNER F	WEIGHT
4+6 x GN 1/1 80mm spacing	W: 525mm D: 770mm H: 1350mm	W: 330mm D: 540mm H: 508mm	W: 330mm D: 540mm H: 348mm	62 kg

Neutral + 230V/1000W
Product number: 122060-036F
 SDX Thermobox SF150 (4+6 GN 1/1)

SF180



GUIDES	OUTER	INNER S	INNER F	WEIGHT
6+6 x GN 1/1 80mm spacing	W: 525mm D: 770mm H: 1510mm	W: 330mm D: 540mm H: 508mm	W: 330mm D: 540mm H: 508mm	65 kg

Neutral + 230V/1000W
Product number: 122105-036F
 SDX Thermobox SF180 (6+6 GN 1/1)

SF210



GUIDES	OUTER	INNER S	INNER F	WEIGHT
4+10 x GN 1/1 80mm spacing	W: 525mm D: 770mm H: 1795mm	W: 330mm D: 540mm H: 828mm	W: 330mm D: 540mm H: 348mm	80 kg

Neutral + 230V/1000W
Product number: 122065-036
 SDX Thermobox SF210 (4+10 GN 1/1)

SF240



GUIDES	OUTER	INNER S	INNER F	WEIGHT
8+8 x GN 1/1 80mm spacing	W: 920mm D: 770mm H: 1190mm	W: 330mm D: 540mm H: 668mm	W: 330mm D: 540mm H: 668mm	90 kg

Neutral + 230V/1000W
Product number: 122066-036
 SDX Thermobox SF240 (8+8 GN 1/1)

THERMOBOX® SF – NEUTRAL AND CONVECTION HEATING COMBINATION

SF360



GUIDES	OUTER	INNER S	INNER F	WEIGHT
12 + 12 x GN 1/1 80mm spacing	W: 920mm D: 770mm H: 1355mm	W: 330mm D: 540mm H: 1000mm	W: 330mm D: 540mm H: 1000mm	115 kg

Neutral + 230V/1000W
Product number: 122046-03F
 SDX Thermobox SF360 (12+12 GN 1/1)

12 | 12

SF420



GUIDES	OUTER	INNER S	INNER F	WEIGHT
14 + 14 x GN 1/1 80mm spacing	W: 920mm D: 770mm H: 1515mm	W: 330mm D: 540mm H: 1160mm	W: 330mm D: 540mm H: 1160mm	126 kg

Neutral + 230V/1000W
Product number: 122067-036
 SDX Thermobox SF420 (14+14 GN 1/1)

14 | 14



THERMOBOX® SF - Technical specifications

Exterior walls: ABS plastic.

Inner container: Welded container in stainless steel.

Guides: Stainless steel, pressed from the inner container.

Insulation: Polyurethane foam.

Door: Internal surface made of smooth and seamless stainless steel. Exterior in ABS plastic with bolt lock and door mounted handle for one-handed grip.

Wheels: Hot-dip galvanized steel. 160 mm wheels with rubber tires, two brakes and 2 fixed.

Top frame: Stainless steel and PVC corners.

Trolley frame: Rejected list of galvanized steel coated with PVC.

S: Neutral

F: Efficient convection heating system, with electronic temperature control, insulation class IP 44, 230V/1000W. CE and S mark.

BANQUET SF



GUIDES	OUTER	INNER S	INNER F	WEIGHT
17 + 17 x GN 2/1 80mm spacing	W: 1445mm D: 770mm H: 1740mm	W: 535mm D: 667mm H: 1405mm	W: 535mm D: 667mm H: 1405mm	249 kg

Neutral + 230V/1350W/6A
Product number: 122254-01S
 Banquet SF (17+17 GN 2/1)

17 | 17

THERMOBOX® CE – ACTIV COOLING AND ELECTRIC HEATING COMBINATION

CE120



GUIDES	OUTER	INNER C	INNER E	WEIGHT
4+4 x GN 1/1 80mm spacing	W: 525mm D: 805mm H: 1190mm	W: 330mm D: 540mm H: 348mm	W: 330mm D: 540mm H: 348mm	70 kg

AA120/180W + 230V/280W
Product number: 122300-03
 SDX Thermobox CE120 (4+4 GN 1/1)

CE150



GUIDES	OUTER	INNER C	INNER E	WEIGHT
4+6 x GN 1/1 80mm spacing	W: 525mm D: 805mm H: 1350mm	W: 330mm D: 540mm H: 348mm	W: 330mm D: 540mm H: 508mm	70 kg

AA120/180W + 230V/500W
Product number: 122211-03
 SDX Thermobox CE150 (4+6 GN 1/1)

CE180



GUIDES	OUTER	INNER C	INNER E	WEIGHT
4+8 x GN 1/1 80mm spacing	W: 525mm D: 805mm H: 1635mm	W: 330mm D: 540mm H: 348mm	W: 330mm D: 540mm H: 668mm	75 kg

AA120/180W + 230V/500W
Product number: 122203-03
 SDX Thermobox CE180 (4+8 GN 1/1)

CE180



GUIDES	OUTER	INNER C	INNER E	WEIGHT
6+6 x GN 1/1 80mm spacing	W: 525mm D: 805mm H: 1510mm	W: 330mm D: 540mm H: 508mm	W: 330mm D: 540mm H: 508mm	75 kg

AA120/180W + 230V/500W
Product number: 122215-03
 SDX Thermobox CE180 (6+6 GN 1/1)

THERMOBOX® CE – ACTIV COOLING AND ELECTRIC HEATING COMBINATION

CE210



GUIDES	OUTER	INNER C	INNER E	WEIGHT
6+8 x GN 1/1 80mm spacing	W: 525mm D: 805mm H: 1955mm	W: 330mm D: 540mm H: 508mm	W: 330mm D: 540mm H: 668mm	85 kg

AA120/180W + 230V/500W
Product number: 122251-03
 SDX Thermobox CE210 (6+8 GN 1/1)

CE240



GUIDES	OUTER	INNER C	INNER E	WEIGHT
8+8 x GN 1/1 80mm spacing	W: 920mm D: 805mm H: 1190mm	W: 330mm D: 540mm H: 668mm	W: 330mm D: 540mm H: 668mm	100 kg

AA120/180W + 230V/500W
Product number: 122262-036
 SDX Thermobox CE240 (8+8 GN 1/1)

CE360



GUIDES	OUTER	INNER C	INNER E	WEIGHT
12 + 12 x GN 1/1 80mm spacing	W: 920mm D: 825mm H: 1355mm	W: 330mm D: 540mm H: 1000mm	W: 330mm D: 540mm H: 1000mm	115 kg

AA120/180W + 230V/800W
Product number: 122046-03F
 SDX Thermobox CE360 (12+12 GN 1/1)



THERMOBOX® CE - Technical specifications

Exterior walls: ABS plastic.

Inner container: Welded container in stainless steel.

Guides: Stainless steel, pressed from the inner container.

Insulation: Polyurethane foam.

Door: Internal surface made of smooth and seamless stainless steel. Exterior in ABS plastic with bolt lock and door mounted handle for one-handed grip.

Wheels: Hot-dip galvanized steel. 160 mm wheels with rubber

tires, two brakes and 2 fixed.

Top frame: Stainless steel and PVC corners.

Trolley frame: Reject list of galvanized steel coated with PVC.

C: Efficient compact chillers with electronic temperature control AA120, 27 V DC. 230V/245W AC, insulation class IP44.

E: Patented, efficient heating system, with electronic temperature control Foil elements, insulation class IP 44, 230V/800W. CE and S mark.

THERMOBOX® CF – ACTIV COOLING AND CONVECTION HEATING COMBINATION

CF150



GUIDES	OUTER	INNER C	INNER F	WEIGHT
4+6 x GN 1/1 80mm spacing	W: 525mm D: 805mm H: 1350mm	W: 330mm D: 540mm H: 348mm	W: 330mm D: 540mm H: 508mm	70 kg

AA120/180W + 230V/1000W
Product number: 122282-03
 SDX Thermobox CF150 (4+6 GN 1/1)

CF180



GUIDES	OUTER	INNER C	INNER F	WEIGHT
6+6 x GN 1/1 80mm spacing	W: 525mm D: 805mm H: 1510mm	W: 330mm D: 540mm H: 508mm	W: 330mm D: 540mm H: 508mm	75 kg

AA120/180W + 230V/1000W
Product number: 122215-03F
 SDX Thermobox CF180 (6+6 GN 1/1)

CF180



GUIDES	OUTER	INNER C	INNER F	WEIGHT
4+8 x GN 1/1 80mm spacing	W: 525mm D: 805mm H: 1635mm	W: 330mm D: 540mm H: 348mm	W: 330mm D: 540mm H: 668mm	75 kg

AA120/180W + 230V/1000W
Product number: 122284-03
 SDX Thermobox CF180 (4+8 GN 1/1)

CF210



GUIDES	OUTER	INNER C	INNER F	WEIGHT
6+8 x GN 1/1 80mm spacing	W: 525mm D: 805mm H: 1925mm	W: 330mm D: 540mm H: 508mm	W: 330mm D: 540mm H: 668mm	80 kg

AA120/180W + 230V/1000W
Product number: 122251-03F
 SDX Thermobox CF210 (6+8 GN 1/1)

THERMOBOX® CF – ACTIV COOLING AND CONVECTION HEATING COMBINATION

CF240	GUIDES	OUTER	INNER C	INNER F	WEIGHT
	8+8 x GN 1/1 80mm spacing	W: 920mm D: 805mm H: 1190mm	W: 330mm D: 540mm H: 668mm	W: 330mm D: 540mm H: 668mm	115 kg
	AA120/180W + 230V/1000W Product number: 122068-036 SDX Thermobox CF240 (8+8 GN 1/1)				

8 | 8

CF360	GUIDES	OUTER	INNER C	INNER F	WEIGHT
	12+12 x GN 1/1 80mm spacing	W: 920mm D: 825mm H: 1355mm	W: 330mm D: 540mm H: 1000mm	W: 330mm D: 540mm H: 1000mm	135 kg
	AA120/180W + 230V/1000W Product number: 122220-03F SDX Thermobox CF360 (12+12 GN 1/1)				

12 | 12

CF420	GUIDES	OUTER	INNER C	INNER F	WEIGHT
	14+14 x GN 1/1 80mm spacing	W: 920mm D: 825mm H: 1515mm	W: 330mm D: 540mm H: 1160mm	W: 330mm D: 540mm H: 1160mm	145 kg
	AA120/180W + 230V/1000W Product number: 122069-036 SDX Thermobox CF420 (14+14 GN 1/1)				

14 | 14



THERMOBOX® CF - Technical specifications

Exterior walls: ABS plastic.

Inner container: Welded container in stainless steel.

Guides: Stainless steel, pressed from the inner container.

Insulation: Polyurethane foam.

Door: Internal surface made of smooth and seamless stainless steel. Exterior in ABS plastic with bolt lock and door mounted handle for one-handed grip.

Wheels: Hot-dip galvanized steel. 160 mm wheels with rubber tires, two brakes and 2 fixed.

Top frame: Stainless steel and PVC corners.

Trolley frame: Reject list of galvanized steel coated with PVC.

C: Efficient compact chillers with electronic temperature control AA120, 27 V DC. 230V/245W AC, insulation class IP44.

F: Efficient convection heating system, with electronic temperature control, insulation class IP 44, 230V/1000W. CE and S mark.

THERMOBOX® KE – COMPRESSOR COOLING AND ELECTRIC HEATING COMBINATION

KE180



GUIDES	OUTER	INNER K	INNER E	WEIGHT
6+6 x GN 1/1 80mm spacing	W: 920mm D: 765mm H: 1115mm	W: 330mm D: 540mm H: 505mm	W: 330mm D: 540mm H: 505mm	104 kg

230V/245W AC + 230V/500W
Product number: 122072-036
 SDX Thermobox KE180 (6+6 GN 1/1)

KE210



GUIDES	OUTER	INNER K	INNER E	WEIGHT
6+8 x GN 1/1 80mm spacing	W: 920mm D: 765mm H: 1275mm	W: 330mm D: 540mm H: 665mm	W: 330mm D: 540mm H: 505mm	110 kg

230V/245W AC + 230V/500W
Product number: 122073-036
 SDX Thermobox KE210 (6+8 GN 1/1)

KE240




GUIDES	OUTER	INNER K	INNER E	WEIGHT
8+8 x GN 1/1 80mm spacing	W: 920mm D: 765mm H: 1275mm	W: 330mm D: 540mm H: 665mm	W: 330mm D: 540mm H: 665mm	115 kg

230V/245W AC + 230V/500W
Product number: 122074-036
 SDX Thermobox KE240 (8+8 GN 1/1)

THERMOBOX® KE – COMPRESSOR COOLING AND ELECTRIC HEATING COMBINATION

KE360

	GUIDES	OUTER	INNER K	INNER E	WEIGHT
	12+12 x GN 1/1 80mm spacing	W: 920mm D: 765mm H: 1605mm	W: 330mm D: 540mm H: 1000mm	W: 330mm D: 540mm H: 1000mm	125 kg
	230V/245W AC + 230V/800W Product number: 122077-036 SDX Thermobox KE240 (12+12 GN 1/1)				

12 | 12



THERMOBOX® KE - Technical specifications

Exterior walls: ABS plastic.

Inner container: Welded container in stainless steel.

Guides: Stainless steel, pressed from the inner container.

Insulation: Polyurethane foam.

Door: Internal surface made of smooth and seamless stainless steel. Exterior in ABS plastic with bolt lock and door mounted handle for one-handed grip.

Wheels: Hot-dip galvanized steel. 160 mm wheels with rubber tires, two brakes and 2 fixed.

Top frame: Stainless steel and PVC corners.

Trolley frame: Rejected list of galvanized steel coated with PVC.

K: Efficient convection cooling with electronic temperature control 230V/245W/1.8A, insulation class IP44.

E: Patented, efficient heating system, with electronic temperature control Foil elements, insulation class IP 44. CE and S mark.

THERMOBOX® KF – COMPRESSOR COOLING AND CONVECTION HEATING COMBINATION

6
6

KF180



GUIDES	OUTER	INNER K	INNER F	WEIGHT
6+6 x GN 1/1 80mm spacing	W: 920mm D: 770mm H: 1570mm	W: 330mm D: 540mm H: 508mm	W: 330mm D: 540mm H: 508mm	134 kg
230V/245W AC + 230V/1000W Product number: 122215-03KF SDX Thermobox KF180 (6+6 GN 1/1)				

8
8

KF240



GUIDES	OUTER	INNER K	INNER F	WEIGHT
8+8 x GN 1/1 80mm spacing	W: 920mm D: 770mm H: 1275mm	W: 330mm D: 540mm H: 668mm	W: 330mm D: 540mm H: 668mm	142 kg
230V/245W AC + 230V/1000W Product number: 122262-03KF SDX Thermobox KF240 (8+8 GN 1/1)				

10
10

KF300



GUIDES	OUTER	INNER K	INNER F	WEIGHT
10+10 x GN 1/1 80mm spacing	W: 920mm D: 770mm H: 1435mm	W: 330mm D: 540mm H: 828mm	W: 330mm D: 540mm H: 828mm	150 kg
230V/245W AC + 230V/1000W Product number: 122219-03KF SDX Thermobox KF300 (10+10 GN 1/1)				

THERMOBOX® KF – COMPRESSOR COOLING AND CONVECTION HEATING COMBINATION

KF360

	GUIDES	OUTER	INNER K	INNER F	WEIGHT
	12+12 x GN 1/1 80mm spacing	W: 920mm D: 770mm H: 1605mm	W: 330mm D: 540mm H: 1000mm	W: 330mm D: 540mm H: 1000mm	160 kg
	230V/245W AC + 230V/1000W Product number: 122220-03KF SDX Thermobox KF360 (12+12 GN 1/1)				

12 | 12



THERMOBOX® KF - Technical specifications

Exterior walls: Stainless steel

Inner container: Welded container in stainless steel.

Guides: Stainless steel, pressed from the inner container.

Insulation: Polyurethane foam.

Door: Stainless steel door with bolt lock and door mounted handle for one-handed grip. Smooth seamless surface internally.


Wheels: Hot-dip galvanized steel. 160 mm wheels with rubber tires, two brakes and 2 fixed.

Mobile base: Stainless. Reject List of PVC.

K: Efficient convection cooling with electronic temperature control 230V/245W/1.8A, insulation class IP44.

F: Efficient convection heating system, with electronic temperature control, insulation class IP 44, 230V/1000W. CE and S mark.

BANQUET KF

	GUIDES	OUTER	INNER K	INNER F	WEIGHT
	13+17 x GN 2/1 80mm spacing	W: 1445mm D: 890mm H: 1740mm	W: 535mm D: 667mm H: 1120mm	W: 535mm D: 667mm H: 1455mm	265 kg
	230V/245W + 230V/1350W. 6 Wheels. Product number: 122255-01KF SDX Thermobox KF (13+17 GN 1/1)				

13 | 17

PORTABLE THERMOBOX®

The portable Thermobox® are designed to be compatible with Gastronorm containers, maximum depth 100mm and 200mm respectively.



S30



GUIDES

4 x GN 1/2
80mm spacing

MEASUREMENTS

W 425mm
D 380mm
H 415mm

WEIGHT

9,5 kg

Neutral

Aluminium external walls and all-welded inner container Polyurethane insulation
Aluminium door with eccentric lock

Plastic stacking corners with stainless steel fittings and handles

Product number: 122001 SDX Thermobox S30 (4 GN 1/2)

E30



GUIDES

4 x GN 1/2
80mm spacing

MEASUREMENTS

W 425mm
D 380mm
H 415mm

WEIGHT

10,5 kg

Heating section – 230V/145W

Aluminium external walls and all-welded inner container Polyurethane insulation
Aluminium door with eccentric lock

Plastic stacking corners with stainless steel fittings and handles

Product number: 122002 SDX Thermobox E30 (4 GN 1/2)

S600



GUIDES

4 x GN 1/1
80mm spacing

MEASUREMENTS

W 425mm
D 645mm
H 415mm

WEIGHT

13 kg

Neutral

Aluminium external walls and all-welded inner container Polyurethane insulation
Aluminium door with eccentric lock

Plastic stacking corners with stainless steel fittings and handles

Product number: 122005 SDX Thermobox S600 (4 GN 1/1)

E600



GUIDES

4 x GN 1/1
80mm spacing

MEASUREMENTS

W 425mm
D 645mm
H 415mm

WEIGHT

14,5 kg

Heating section – 230V/280W IP44

Aluminium external walls and all-welded inner container Polyurethane insulation
Aluminium door with eccentric lock

Plastic stacking corners with stainless steel fittings and handles

Product number: 122006-04 SDX Thermobox E 600 (4 GN 1/1)

Optional extras

Cooling plate

141002

Thermometer in door

123007



TROLLEYS FOR PORTABLE THERMOBOX AND FLEXI FOR GROCERIES



H62

MEASUREMENTS

WEIGHT



W 660mm
D 440mm
H 175mm

5 kg

Adapted for: S600 & E600.
Maximum load 200kgs.
Zinc-plated angle profile construction.
100mm castors, 2 fixed and 2 swivel castors with brakes.
Product number: 131001

H68

MEASUREMENTS

WEIGHT



W 470mm
D 670mm
H 200mm (900mm with handle)

13 kg

Adapted for: S600 & E600
Maximum load 200kgs
Stainless steel construction 18/8
125mm castors with rubber track, 2 fixed and 2 swivel castors with brakes
Product number: 132001

H78

MEASUREMENTS

WEIGHT



W 450mm
D 660mm
H 450mm (900mm with handle)

13 kg

Adapted for: S600 & E600
Maximum load 200kgs
Stainless steel construction 18/8
125mm castors with rubber track, 2 fixed and 2 swivel castors with brakes
Product number: 132002

H78S

MEASUREMENTS

WEIGHT



W 480mm
D 660mm
H 630mm (900mm with handle)

17,5 kg

Adapted for: S600 & E600
Maximum load 200kgs
Stainless steel construction 18/8
125mm castors with rubber track, 2 fixed and 2 swivel castors with brakes
Top platform – height 630mm. Bottom platform – height 200mm
Product number: 132003

FLEXI

OUTER MEASUREMENTS

OUTER MEASUREMENTS

WEIGHT



W 435mm
D 695mm
H 1265mm

W 405mm
D 625mm
H 1100mm

40 kg

The door can be locked in the closed or open position.
125 mm wheels with rubber tires, 2 braked and 2 fixed.
Can be fitted with towing equipment.
Product number: 135001 Combi Wagon SDX Flexi

OPTIONAL EXTRAS

We have a wide range of optional extras for the SDX® Thermobox® to create the perfect tool for your food transportation needs

All stainless

Both inside and outside in all stainless. A stylish and hygienic choice.



Window in the door

Optional glass window in the door allows you to quickly and easily check the contents of your Thermobox® without affecting the temperature.

Ergonomic central brake

Practical and ergonomic central brake simplifies the management of everyday life.



Eccentric lock

As an option to the bolt lock with door mounted handle we offer a sturdy eccentric lock.

UNIQUE EXTERIOR...

...the same quality on the inside

SDX® now gives you the opportunity to create a completely unique Thermobox® with your own colour and your own logo. Obviously with the same high quality and durability as always.



Choose your colour



Now you can choose the colour of your Thermobox®. To suit your interior or to easily distinguish between different types of boxes.

All stainless



Both inside and outside in all stainless. A stylish and hygienic choice.

Your logo



Standard colours



All our Thermobox® can be delivered in one of our three standard colours blue, red or black. Timeless colours that suit all environments and settings.

It is important to stand out from the crowd

Do you want to create an even clearer identity, there is the opportunity to decorate the boxes with both your logo or images from your graphical profile.

With your logo on SDX® Thermobox® you can proudly transport your meals while marketing your business.

MAKE YOUR OWN COMBINATION



If you are struggling to find the perfect combination for your needs we can help you combine your own Thermobox. We can combine all our modules from the smallest volume with 4 guides to our largest volume with 14 guides.

Please contact us about your food transportation needs and we will give you the solution.



Market leader in the Nordic region

SDX® develops, manufactures and markets insulated boxes for transport and storage of temperature sensitive products under the brand SDX® THERMOBOX®.

Special features of the SDX® are high quality in every detail, continuous product and personalized service.

In our factory are produced annually thousands boxes for users primarily in the Nordic countries but also to export markets in Europe and beyond

Own production for the highest quality

SDX® has all the production is based in Sölvesborg in Blekinge, Sweden.

All our products are manufactured with the "all stainless interior" ie pressed guides in stainless steel inner container. A unique technology that provides unsurpassed durability, easy cleaning and enhances safety.



